

Leak sealing lance



- Ready to use in seconds
- Only one person required for setup
- For sealing cracks and holes
- Ensures safe distance from leak



www.vetter.de/vetter_emergency/en/Rescue+Products/Sealing+leaks/Leak+sealing+lance.html

The quick fix for sealing leaks.

When you're the first person on the rescue site, the Vetter leak sealing lance enables you to act quickly. With no assistance required, you can seal small leaks in storage tanks, tank trucks or wagons in seconds and from a safe distance. By using the wedge and cone bags at the tip of the leak sealing lance, you will effectively reduce the volume flow rate at cracks measuring 15 - 60 mm (0.6 - 2.3 inch) and holes measuring 30 - 90 mm (1.2 - 3.5 inch). Anti-slip profiles on the bags ensure a good grip. The device with its simple design provides an invaluable quick-fix which will buy you time to put further measures in place.

Leak sealing lance set with foot pump



Leak sealing lance set with foot pump 150009600

- Wedge bag 6, 8, 11 and cone bag 7 (1.5 bar / 21.75 psi)
- 3 PVC hollow rods (35 cm / 14 inch)
- PVC hollow rod with chain and nipple
- Shut- off unit
- Foot pump with safety valve 1.5 bar (21.75 psi)
- Drip shield
- Transport case 400 x 300 x 220 mm (16 x 12 x 9 inch)

Weight of set, approx.: 8.1 kg (17.9 lbs)

Emergency Pneumatics

Technical data

- Working pressure: 1.5 bar (21.75 psi)
- Test pressure: 1.95 bar (28.5 psi)

* Length with coupling + 6 cm (2.36 inch)

Product	Art. no.	Size (L x W x H) cm / inch	Air requirement, at working pressure litres / cu.ft.	Weight, approx. kg / lbs
Wedge Bag 6	1500009800	23* x 6 x 5 9 x 2,4 x 2	1,5 0,05	0,2 0,4
Wedge Bag 8	1500010000	23* x 8 x 5,5 9 x 8 x 2,2	3,5 0,12	0,3 0,7
Wedge Bag 11	1500010100	23* x 11 x 7 9 x 4,3 x 2,8	7,8 0,28	0,4 0,9
Cone Bag 7	1500010200	23* x Ø 7 9 x Ø 2,8	3,0 0,11	0,2 0,4

Accessories

- Inflation hoses 1.5 bar (21.75 psi)
- Controllers 1.5 bar (21.75 psi)
- Foot pump 1.5 bar (21.75)
- Inflation with cylinder
- Inflation with alternative air source



In operation...

- For cracks 15 - 60 mm (0.6 - 2.3 inch)
- For holes 30 - 90 mm (1.2 - 3.5 inch)



Good reasons...

- One- person operation
- Inflatable with foot pump
- Adequate distance from danger area maintained thanks to 140 cm (55 inch) lance
- Shut- off unit prevents pressure drop and air leakage when decoupling



Guaranteed quality:

- Individually tested (with inspection seal)
- Good resistance to chemicals
- Highly flexible rubber

Please contact us directly should you have any further questions concerning this product.

Sales Germany
Phone.: +49 (0) 22 52 / 30 08-50
Fax: +49 (0) 22 52 / 30 08-70
E- Mail: vetter.info@idexcorp.com

Sales international
Phone.: +49 (0) 22 52 / 30 08-60
Fax: +49 (0) 22 52 / 30 08-71
E- Mail: vetter.info@idexcorp.com

Or find the nearest dealer under:
[www.vetter.de/ support/ haendler](http://www.vetter.de/support/haendler)
