



## 80 PERSONAL PROTECTIVE EQUIPMENT

### *Fire Crossing Suit S200 EN 1486* (Code 80.0106.160)



**OVERALL S204** designed with the rear backpack for housing the breathing apparatus. Front opening closed by double flap and Velcro® F.R, mandarin collar, long sleeves.

**OVER-BOOTS S202** entirely insulated with quilted compound in fireproof fabric. Double sole 100% para-aramid reinforced with anti-absorption silicone.

Back closure with Velcro® F.R.

One size fits all.

Integral internally insulated **HOOD S203**. Compliant for the use of the full-face mask and dispensing unit, equipped with panoramic visor (replaceable) in golden polycarbonate and certified according to EN 166 - EN 136.

Adjustable internal hood certified EN 397.

One size fits all.

**3-Finger GLOVE S201/ 5-Finger GLOVE S208** composed of outer fabric in pre-oxidized aluminized para-aramid fiber 458 g/m<sup>2</sup>. Internally insulated with 6 layers quilted carbon fiber. Velcro® F.R fastening strap on the forearm. Inserts in Gripstop on thumb and forefinger for greater dexterity.

Length: 40 cm.

One size fits all.

The suit is furnished in a black carrying bag in PVC

Available Sizes: I (M/L) - II (XL/XXL)

**FCL FIRE CROSS LIGHT COMPOUND** Innovative compound designed to reduce the weight and the thickness of the fire crossing suits improving mobility and operators' comfort, without compromising the high heat resistance performance. **COMPOSITION:** aluminized fabric 100% aramid of 520 g/m<sup>2</sup> OXISTOP 485: n.3 layers of 100% pre-oxidized felt 120 g/m<sup>2</sup> + n.1 layer of lining 50% aramid and 50% viscose FR 120 g/m<sup>2</sup>

Standard: EN 1486 - PPE of III Category

WEIGHT OF THE COMPLETE SUIT (excluding the carrying bag) = 7,40 kg

