

## SPRINKLER F2A CI HI3 SRC



**STANDARD:** EN 15090:2012

**UPPER:** full grain fireproof and water repellent leather

**EXTERNAL LINING:** breathable leather

**INTERNAL LINING:** COFRA-TEX WATERPROOF UNIVERSAL membrane with WATERPRO-TECH construction system

**FOOTBED:** HEAT BARRIER, made of soft and scented polyurethane, antistatic, anatomic, insulating against high temperatures, covered with cloth. The thermal comfort inside the footwear is granted thanks to the special polyurethane compound devised to give high insulation

**SOLE:** fully made of nitrile rubber resistant to +300 °C (1 minute contact)

**TOE CAP:** steel resistant to 200 J

**MIDSOLE:** non metallic APT PLATE - Zero Perforation

**WIDTH:** 12 Mondopoint

**PLUS:** fire resistant aramid laces, Nitrile rubber toe cap protection, padded back area, quick release with easy grab zip puller, rear leather pull up loop, side reflex bands for high visibility, triple and quadruple fireproof stitchings

**PERFORMANCES AND TECHNICAL FEATURES:** Cold Protection (CI), Heat Resistant (HI), Italian Leather, toe cap protection, Water Resistant, with zip

**SUGGESTED USAGE:** footwear for firemen, footwear for forest fire

**SIZES:** 40-48 (EU), 6½-13 (UK)



EN 15090:2012

### PERFORMANCES



### TECHNOLOGIES AND MATERIALS

